

TECHNICAL DATA • TECHNISCHE DATEN • TECHNISCHE GEGEVENS • FICHE TECHNIQUE

Article Seaming tape C345

Artikel Nahtband C345
 Artikel Lijmband C345
 Article Bande de jonction C345

Composition Spunbonded Polyester 120 g/m² laminated with 20µm PE foil and Spunbonded Polyester 48 g/m² on the backside

Quality characteristic Qualitätsmerkmal Kwaliteitskenmerken Caractéristique qualitative	Technical data Technische Daten Technische gegevens Fiche technique	Test method Prüfmethode Testmethode Contrôle d'après
Weight Gewicht Gewicht Masse surfacique	218 g/m ²	DIN EN 29073-1
Thickness Dicke Dikte Epaisseur	0.68 mm	DIN EN ISO 9073-2
Tensile Strength MD Höchstzugkraft Länge Trekweerstand lengte Résistance à la traction longueur	480 (N/50 mm)	DIN EN 29073-3
Tensile Strength CD Höchstzugkraft quer Trekweerstand breedte Résistance à la traction largeur	260 (N/50 mm)	DIN EN 29073-3
Elongation at break MD Höchstzugdehnung längs Rek bij breuk lengte Élongation à la rupture longueur	23%	DIN EN 29073-3
Elongation at break CD Höchstzugdehnung quer Rek bij breuk breedte Élongation à la rupture largeur	26%	DIN EN 29073-3

The figures represent average values and are as such indicative.

The user must always test the suitability of the product for the intended use. The user bears all associated risks and liabilities. KING Sports B.V. is not liable for any damage as a consequence of unsuitable use of the product. The data given applies to the seaming tape as supplied, before gluing. Values after gluing will depend on the types of glue, artificial turf and artificial turf system used at the installation.